

New Brunswick Laboratory U.S. Department of Energy

Certificate of Analysis CRM U0002 Uranium Isotopic Standard

1 g Uranium as U_3O_8

	²³⁴ U	²³⁵ U	²³⁶ U	²³⁸ U
Atom Percent:	0.00016	0.01755	<0.00001	99.9823
Uncertainty:	±0.00001	±0.00005	-	±0.0001
Weight Percent:	0.00016	0.01733	<0.00001	99.9825

This Certified Reference Material (CRM) is primarily intended for the calibration of mass spectrometers used to perform uranium isotopic measurements. The specific purpose of this isotopic standard is for the determination of mass discrimination effects for uranium isotopes being measured under similar analytical conditions. Each unit of CRM U0002 consists of approximately 1 gram of uranium, in the form of highly purified U_3O_8 , contained in a glass bottle.

The indicated uncertainties for the isotopic composition of the CRM are 95% confidence intervals for a single determination. This term can be defined as an approximate two-sigma limit, where sigma is the standard deviation of the measurements data obtained from the material. The uncertainties include allowances for inhomogeneity of the material as well as analytical error.

This CRM was originally issued in 1970 by the National Bureau of Standards (NBS) as Standard Reference Material (SRM) U-0002. The measurements made at NBS leading to the certification were performed by E. L. Garner, L. A. Machlan and L.J. Moore under the direction of W. R. Shields. In 1987, the technical and administrative transfer of NBS Special Nuclear SRMs into the NBL CRM Program was coordinated by the NBS Office of Standard Reference Materials and N. M. Trahey, NBL.

The ²³⁵U abundance of the CRM was determined by isotope dilution mass spectrometry (IDMS) using high-purity ²³³U as a spike. The ²³⁵U/²³⁸U measurements were made on a single stage thermal ionization mass spectrometer equipped with a Faraday cup detection system.

The 234 U abundance was similarly determined by isotope dilution mass spectrometry using 233 U and a two-stage thermal ionization mass spectrometer equipped with a pulse-counting system.

All isotopic corrections for mass discrimination effects were based upon concurrent analyses of CRM U500 (formerly SRM U-500).

NOTE: NBS Special Publication 260-27 presents further details of the measurements made at NBS which provided the basis for the certification, and is available from the NBS Office of Standard Reference Materials

March 30, 2008 Argonne, Illinois

www.nbl.doe.gov Page 1 of 1 Jon Neuhoff, Director New Brunswick Laboratory

(Editorial revision of Certificate dated October 1, 1987)