

DOE-NP Accelerator R&D PI Meeting

P. Adderley, D. Bullard, J. Grames, J. Hansknecht,
C. Hernandez-Garcia, Md. Abdullah Mamun, M. Poelker,
M. Stutzman, R. Suleiman, S. Zhang

Students: W. Liu, Y. Wang



DOE Headquarters, Germantown 11/14/2016

RECENTLY FUNDED PROJECTS

- 500kV DC High Voltage Inverted Gun with Load-locked CsK₂Sb Deposition Chamber - Research and Development for Next Generation Nuclear Physics Accelerator Facilities (LAB 12-632) **and** (LAB 14-1082)
- New Photocathode Materials for Electron Ion Colliders - Research and Development for Next Generation Nuclear Physics Accelerator Facilities (LAB 12-632) **and** (LAB 14-1082)
- Cryo-Pumped DC High Voltage Polarized Electron Source - Small Project, DOE Office of Nuclear Physics, (LAB 10-339)

RECENTLY FUNDED PROJECTS

- 500kV DC High Voltage Inverted Gun with Load-locked CsK₂Sb Deposition Chamber - Research and Development for Next Generation Nuclear Physics Accelerator Facilities (LAB 12-632) **and** (LAB 14-1082)
- New Photocathode Materials for Electron Ion Colliders - Research and Development for Next Generation Nuclear Physics Accelerator Facilities (LAB 12-632) **and** (LAB 14-1082)
- Cryo-Pumped DC High Voltage Polarized Electron Source - Small Project, DOE Office of Nuclear Physics, (LAB 10-339)

RECENTLY FUNDED PROJECTS

Summary of expenditures by fiscal year (FY):

\$K	FY10+FY11	FY12+FY13	FY14+FY15	FY16	Totals
a) Funds allocated		\$116.0			\$116.0
b) Actual costs to date		\$116.0			\$116.0

LAB 12-632 & LAB 14-1082 - 500kV DC High Voltage Inverted Gun with Load-Locked Csk₂sb Deposition Chamber

\$K	FY10+FY11	FY12+FY13	FY14+FY15	FY16	Totals
a) Funds allocated		\$44.0			\$44.0
b) Actual costs to date		\$44.0			\$44.0

LAB 12-632 & LAB 14-1082 - New Photocathode Materials for Electron Ion Colliders (used by W&M for plasmonic photocathode studies)

\$K	FY10+FY11	FY12+FY13	FY14+FY15	FY16	Totals
a) Funds allocated	\$362.0				\$362.0
b) Actual costs to date	\$361.6				\$361.6


LAB 10-339 - Cryo-Pumped DC High Voltage Polarized Electron Source

To extend the “inverted gun” geometry design, to operate at higher voltage, for high bunch charge and high average current EIC cooling applications

To design a photocathode test stand to measure QE and polarization of new photocathode materials that might help EIC


To improve photogun vacuum and thereby improve lifetime of polarized electron sources, particularly at mA current, i.e., eRHIC

The CEBAF - ILC Inverted Gun




- Load-locked GaAs polarized photogun
- 130 kV at CEBAF, 200 kV at Injector Test Stand
- Gun Vacuum \sim low 10^{-12} Torr

500 kV PHOTOGUN?




CEBAF 130 kV Inverted Gun
"R28" insulator



Longer "R30" insulator
Spherical electrode


BUILDING THE 500 kV GUN

- Start with “dummy” electrodes and test different insulators and cathode screening electrode




INSULATORS AND SCREENING ELECTRODE

- Longer R30 insulators, conventional alumina
- Short R28 insulator, bulk resistivity, mildly conductive
- Longer R30 insulator, bulk resistivity, mildly conductive
- ZrO-coated R30 insulator, also mildly conductive
- dummy electrode with a screening electrode (shed)



BREAKDOWN AT CABLE/INSULATOR INTERFACE

- Problems at the cable junction, atmosphere side



- Note: Field emission was managed via krypton-processing. i.e., voltage first applied with $\sim 10^{-5}$ Torr krypton added to gun chamber


SUMMARY OF TESTS

- Two and 1/2 configurations reached our voltage goal

Insulator type	Length (cm)	Transversal resistivity (Ohm-cm)	Dielectric constant ϵ_1/ϵ_0	Maximum voltage (kV)	Performance
R30 sample 1	20	5.0×10^{15}	9.1	329	Breakdown and puncture near high voltage end
R30 sample 2	20	5.0×10^{15}	9.1	300	Breakdown
R30 with additional screening electrode	20	5.0×10^{15}	9.1	375	370 kV with krypton 4-hr soak, 350 kV in vacuum 4-hr soak. Significant field emission in both cases
R30 ZrO-coated	20	5.0×10^{15}	9.1	340	Breakdown and puncture near ground end
R28 doped	13	7.4×10^{15}	8.4	360	360 kV with krypton 1-hr soak, 350kV in vacuum 5-hr soak, 2 times Minimal field emission in both cases
R30 doped	20			360	Breakdown originating at high voltage end and puncture near ground end



LINEAR POTENTIAL DROP

- Want a linear potential gradient along length of the insulator




- Note - POISSON does not accurately model the mildly-conductive feature of the black insulator

- Combine the two features that provided incremental success: screening electrode and doped black R30 insulator



- Replaced dummy ball with electrode that can hold photocathode

The gap between shed and insulator




CsK₂Sb DEPOSITION CHAMBER



- Effusion source, compact, high capacity
- Contains both Cs and K species, co-deposition
- Photocathodes grown on stalks

Distinguishing QE Drop due to Contamination

Work of M.A. Mamun




- **Systematic decrease in QE at RT in repeated cooling events**
- Considerable **increase in water partial pressure** during brief heating was observed
- **Rejuvenation of QE** by **brief heating at 170-200 °C** was **consistently observed** in the non-baked system which can be considered as a **signature of water adsorption**

Reproducible QE - Cryocooled Photocathode

baked vacuum $\sim 10^{-9}$ Pa


Work of M.A. Mamun

QE (baked chamber)





- The QE at RT **did not show any decrease** between **repeated cooling** events
- **QE at Liquid N₂** temperature (77 K) showed **similar QE every time** it was cooled
- **Initial QE rise** due to **stoichiometric optimization**
- We did our spectral response and temperature analysis from this photocathode.

DEPO CHAMBER AT GUN TEST STAND




Always something to fix: Valve between gun and depo chamber leaked, working distance between puck and chemical sources too large, no mask to limit active area


300 kV Inverted Gun and CsK₂Sb Photocathode



Learning how to use the new photocathode



500 kV GUN



500 kV GUN



Barrel-Polished Electrodes



- Gun electrodes traditionally polished using sand paper and diamond paste
- Tedious process, takes about 30 days to complete
- Now performed in 1 day using SRF barrel polishing machine



From machine shop




30 minutes with plastic cones





30 minutes with corncob

MAGNETIZED BEAM TESTS





Fixed the gun and deposition chamber, added solenoid

350 kV Gun at Injector Test Facility




Old and New inverted guns
Vacuum low 10^{-12} Torr
Working on the beamline now

kV beamline at Injector Test Facility




Plan Z



- Our plan to reach 500 kV
- Combination of long doped insulator and shed, SF6 and epoxy receptacle
- And likely a different vacuum chamber


- $r1 = 1 \text{ cm}$
- $r2 = 2.5 \text{ cm}$
- $r3 = 9.5 \text{ cm}$
- 3 mm gap



Work of Yan Wang

Plan Z

- We have the big insulators
- Cables in Receptacles: very reliable
- Receptacles in SF6: very reliable
- Use cold SF6 to remove heat from photocathode



Thank You

- Will continue to work on 500 kV inverted gun, CsK₂Sb deposition chamber (and Cryopumped gun)
- Magnetized beam tests
- We can revisit high current (mA) lifetime tests with polarized beam but need support