



U.S. DEPARTMENT OF  
**ENERGY**

Office of Science

BERKELEY  
LAB



# Development of a MARS superconducting cold mass for future generations of ECRIS

Damon Todd

November 17, 2025

# Acknowledgements

## **88-Inch Cyclotron, Nuclear Science Division, LBNL**

Brian Bell, Janilee Benitez, Patrick Coleman, Jaime Cruz Duran, Jeff Hansen, Rae de Leon, Jacob Melendrez, Roman Nieto, Larry Phair, Chris Reardon, Nathan Seidman, Daniel Xie, Lianrong Xu, and Sean Zhong

## **Superconducting Magnet Program, Accelerator Technology and Applied Physics Division, LBNL**

Paolo Ferracin, Jose Luis Rudeiros Fernandez, Simone Johnson, Mariusz Juchno, Tom Lipton, Ryan Norris, Soren Prestemon, Matt Reynolds, James Swanson, Chet Spencer, Li Wang, and Ye Yang

This material is based upon work supported by the U.S. Department of Energy, Office of Science, Office of Nuclear Science program under Award Numbers DE-FOA-0002670 and DE-FOA-0003261




# Presentation outline



- Electron cyclotron resonance (ECR) ion source introduction
- The MARS-D ion source
- Update on project deliverables and schedule for sub-projects:
  - superconducting coil construction (sub-project 1)
  - cryogenic system design (sub-project 2)
  - advance inductive oven design and construction (sub-project 3)
  - source design beyond MARS-D (sub-project 4)
- Annual Budget

# Electron Cyclotron Resonance (ECR) ion source basics




**Basic superconducting ECR ion source**

## Why one should care about ECR ion sources:

- They can produce ion beams from any element
- They are the source-of-choice for most ion accelerator facilities around the world
- Better sources are a cost-effective means for facility upgrades
- The pathway to higher-performing sources is clear



# ECR ion source construction cheat sheet




## Rule:

- Higher  $B_{\text{ecr}}$  (and associated resonant RF) means higher performance


## Simple why:

- Higher  $B$ , slower radial diffusion and higher electron energy





## Moving to higher fields




### **LBNL's VENUS ECR ion source**

- Maximum ECR fields using a conventional sextupole-in-solenoid design with NbTi
- Operation up to 28 GHz resonant RF




## Moving to higher fields



### LBNL's VENUS ECR ion source

- Maximum ECR fields using a conventional sextupole-in-solenoid design with NbTi
- Operation up to 28 GHz resonant RF



### MARS-D (Mixed Axial and Radial field System - Demonstrator)

- Sextupole provides solenoidal field
- Using NbTi, reach ECR fields ~60% higher than VENUS
- Operation up to 45 GHz resonant RF




# Constructing MARS-D at LBNL



LBNL experience constructing superconducting ECR ion sources:

- VENUS
- FRIB's VENUS copy
- Two additional VENUS near-copies for FRIB being at least partially constructed




## MARS-D Primary challenges:

1. Winding the closed-loop-coil
2. Hexagonal plasma chamber and cryostat bore





# Closed-loop-coil winding process



Tooling to bend ends




Improved technique:

- Use calculated bend locations to pre-bend wire
- Turn time reduction: 1.5 -> 0.6 hour/turn



# Success: closed-loop-coil winding complete




At 2024 NP Accelerator R&D PI Exchange Meeting, closed-loop-coil completion projected by August 2025

**Update:**  
**Closed-loop-coil complete November 2025**


- 24 layers
- 64 turns per layer
- ~ 6 km of NbTi wire




## Some next steps for cold mass



- Solenoid mandrel construction (underway)




- Solenoid winding
- Seal system for epoxy impregnation



- Surround with iron yokes and a compression aluminum sleeve
- Pre-stress system with bladders and keys



# Major milestones for cold mass




## Complete solenoid winding

Milestone date:

- February 2025

Expected completion date:

- March 2026




## Impregnate MARS-D coils

Milestone date

- December 2025

Expected completion date

- June 2026



## Fully energize MARS-D coils

Milestone date

- September 2026

Expected completion date

- September 2026







U.S. DEPARTMENT OF  
**ENERGY**

Office of Science



# MARS-D Cryostat Design

BERKELEY  
LAB





# MARS-D Cryostat Design







# MARS-D Cryostat Design



## Cryocoolers

Drop-in mode PT450 4x  
5x0.9 W@4.2 K, total **18 W**  
65x0.9 W@45 K, total 234 W

AL330  
150W@45K





# MARS-D Cryostat Design




## DC Current

9 feedthroughs

Copper current leads

High-temperature  
superconductor leads



Quench protection










# MARS-D Cryostat Design



Cold mass  
suspension  
x8





## Example: cold mass supports







Support deformation studies

# Hexagonal bore deformation calculations



Deformation [m]






# MARS-D Cryostat




- Cryostat design well underway
- Primary challenges:
  - Hexagonal warm bore
  - Minimization of distance between plasma chamber and superconducting coils



## Major deliverables on track:

- May 2026 final cryostat review
- September 2026 completed documentation





Jacklyn Gates leads superheavy element research at Lawrence Berkeley National Laboratory. MARILYN SARGENT/  
LAWRENCE BERKELEY NATIONAL LABORATORY







- up to  $200\ \mu\text{A}$   $^{50}\text{Ti}^{12+}$  beams from VENUS,  $23.5\ \mu\text{A}$  from cyclotron
- two element 116 particles produced, setting stage for 120 search
- goal: drop 50Ti consumption rates by 70-80% from  $\sim 4\ \text{mg/hour}$






# Inductive oven development



Experimental tests in 2025 of this type of oven showed exit holes hotter than surroundings



# Inductive oven status







## Major deliverables:

- December 2024: Design and construct aiming oven
  - Initial design designed and constructed on time
  - New design constructed November 2025
- May 2025: aiming oven test
  - Initial test: April 2025
  - New test: November 2025
- April 2026: Rhenium oven construction on track
- September 2026: Uranium beam production on track



## Beyond MARS-D: Future ECRIS design



Apply uni-layer concept to ECR ion sources:

- Cable-in-groove simplifies manufacturing and assembly, similar to successful Canted Cosine Theta (CCT) developed at LBL
- Use multiple of these layers to form closed loop coil





# To 60 GHz with REBCO?



## Main magnet design


- 4-layer REBCO sextupole, ID 200 mm.
- Each layer of the sextupole is powered independently to SSL.

## Magnet system

Frequency	60 GHz
$B_{\text{ecr}}$	2.14 T
$B_{\text{inj}}$ (axial)	7.50 T
$B_{\text{mid}}$ (axial)	1.71 T
$B_{\text{ext}}$ (axial)	4.29 T
$B_{\text{chamber}}$	4.29 T

## REBCO stack

Conductor type	see paper*
Tape thickness	0.1 mm
Stack width	4 mm
Stack thickness	2 mm
Number of tapes	20
Assumed B angle	$\perp$ (worst)



Next MARS | BERKELEY LAB

\*Hilton, D. K., A. V. Gavrilin, and U. P. Trociewitz.  
*Superconductor Science and Technology* 28.7 (2015):  
074002.



# Beyond MARS: technology development



## Segmented

- Segmented cable support design has been completed
- Design reduces overall manufacturing complexity and cost for final CNCed (computer numerical control) aluminum mandrel

## Major deliverables on track:

- January 2026: complete 3D design for future ECRIS
- September 2026: fully documented design for future ECRIS

# Expenditures by fiscal year

	2022 FOA		2024 FOA		
	FY23	FY24	FY25	FY26	Additional
Funds allocated (k\$)	999	999	900	850	485
Actual costs to date (k\$)	999	999	747	0	0



Thank you for your  
attention!